

Neo Featured Materials Overview

Material Name	Description	Category	Tensile Strength (ASTM D638M)	Elongation at Break (ASTM D638M)	Tensile Modulus (ASTM D638M)	HDT @ 0.46 MPa (ASTM D648)	Notched Izod Impact (ASTM D256A)	Color	Partner Page
Somos® WaterShed XC 11122	Versatile, good all-round polymer, very easy to use	●	50.4 MPa	15.5%	2,770 MPa	50 °C	25 J/m	Clear	WaterShed XC 11122
Somos® WaterClear Ultra 10122	Versatile, easy to use, exceptional clarity	●	56 MPa	7.5%	2,880 MPa	47 °C	25 J/m	Clear	WaterClear Ultra 10122
Somos® WaterShed Black	Versatile, good all-round polymer, very easy to use	●	50.4 MPa	15.5%	2,770 MPa	50 °C	25 J/m	Black	WaterShed Black
Somos® PerFORM	Very high heat and stiffness, ceramic	●	68 MPa	1.1%	10,500 MPa	269 °C	17 J/m	White	PerFORM
Somos® PerFORM Reflect	Very high heat and stiffness, ceramic, developed for PIV	●	63.3 MPa	0.8%	10,135 MPa	276 °C	17 J/m	Orange	PerFORM Reflect
Somos® Taurus	High heat and toughness, thermoplastic like performance	●	46.9 MPa	24%	2,310 MPa	62-91 °C	47.5 J/m	Charcoal	Taurus
Somos® EvoLve 128	Very tough and durable with great surface finish	●	56.8 MPa	11%	2,694 MPa	52 °C	39 J/m	White	EvoLve 128

Authorized Distributor:



www.cati.com || 888.308.2284

Categories: ● General Purpose ● High Heat ● Tough