

## **Stratasys J55**

The Stratasys J55™ 3D printer combines the quality of Stratasys PolyJet technology with a compact, office-friendly design.

The five material channel, full color printer features a rotating build platform with fixed print head for outstanding surface finish and print quality. Engineered for the office or design studio environment, it features a small footprint and ProAero<sup>™</sup> filtration technology for odor free, silent and low power operation.

The J55 offers a streamlined design-to-print workflow powered by GrabCAD Print<sup>™</sup>. This allows users to import their designs using native CAD files or 3MF file formats. GrabCAD Print also enables Pantone<sup>®</sup> validated color matching. Remote monitoring lets you easily manage your print jobs from outside the office. Additionally, hands-free soluble support removal makes post processing simple and enables the creation of complex parts without compromising accuracy or detail.

Product Specifications	
Model Materials	<ul> <li>VeroCyanV<sup>™</sup></li> <li>VeroMagentaV<sup>™</sup></li> <li>VeroYellowV<sup>™</sup></li> <li>VeroPureWhite<sup>™</sup></li> <li>VeroPureWhite<sup>™</sup></li> </ul>
Support Materials	SUP710™
Build Size/Printing Area	Up to 1,174 cm <sup>2</sup>
Layer Thickness	Horizontal build layers down to 18 microns (0.0007 in.)
Network Connectivity	LAN - TCP/IP
System Size and Weight	651 x 661 x 1551mm (25.63 x 26.02 x 61.06 in.); 228 kg (503 lbs.)
Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)
Power Requirements	100–120 VAC, 50–60 Hz, 6A, 1 phase 220–240 VAC, 50–60 Hz, 3A, 1 phase
Regulatory Compliance	CE, FCC, EAC
Software	GrabCAD Print
Build Modes	High Quality Speed (HQS) – 18.75um
Accuracy	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – $\pm$ 150µ; above 100 mm – $\pm$ 0.15% of part length.**
	Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm $- \pm 180\mu$ ; above 100 mm $- \pm 0.2\%$ of part length.**

\*\*Measured when ambient temperature is 23 °C and relative humidity is 50%.

## **Stratasys Headquarters**

7665 Commerce Way, Eden Prairie, MN 55344 +1 800 801 6491 (US Toll Free) +1 952 937-3000 (Intl) +1 952 937-0070 (Fax)

stratasys.com ISO 9001:2015 Certified 1 Holtzman St., Science Park, PO Box 2496 Rehovot 76124, Israel +972 74 745 4000 +972 74 745 5000 (Fax)



165 N Arlington Hghts Rd, Ste 101 Buffalo Grove, Illinois 60090 888-308-228 cati@cati.com



© 2020 Stratasys Ltd. All rights reserved. Stratasys, Stratasys signet, J55™ and GrabCAD Print™ are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications subject to change without notice. Printed in the USA. PSS\_PJ\_J55\_0320a